

Ph.: +39 (011) 4701510 or 4701511 or 4704541 Fax +39 (011) 4703910 – Email: info@reinol.it

TECHNICAL DATA SHEET

CERAMIC INKS 2768/6

TECHNICAL CHARACTERISTICS

Ceramic 2768/6 are water-based inks formulated for filter system. They can write on different surfaces, both porous and non-porous. If baked they are permanent on ceramic. It is recommended to clean

with soap and water the object to be painted, apply the ink, let it dry at room temperature for 30 minutes and bake at 200°C for 20 to 30 minutes. These inks are not suitable for Food Contact

Colour ref. No:	BLACK 2768/6	YELLOW 2768/6	ORANGE 2768/6	RED 2768/6	BLUE 2768/6
Viscosity BROOKFIELD Small Sample Adapter, Spindle SC4-18, rpm 100 (cps, 25°C)	< 20	< 20	< 20	< 20	< 20
Ph	8,5 ± 1	8,5 ± 1	8,5 ± 1	8,5 ± 1	8,5 ± 1
Specific Gravity (g/mc)	1,15 ± 0,1	1,15 ± 0,1	1,15 ± 0,1	1,15 ± 0,1	1,15 ± 0,1
Toys 2009/48/EC	Over 36 months of age				
Colour ref. No:	GREEN 2768/6	BROWN 2768/6	PINK 2768/6	VIOLET 2768/6	
Viscosity BROOKFIELD Small Sample Adapter,Spindle SC4-18, rpm 100 (cps, 25°C)	< 20	< 20	< 20	< 20	
Ph	8,5 ± 1	8,5 ± 1	8,5 ± 1	8,5 ± 1	
Specific Gravity (g/mc)	1,15 ± 0,1	1,15 ± 0,1	1,15 ± 0,1	1,15 ± 0,1	
Toys 2009/48/EC	Over 36 months of age				

SUITABLE COMPONENTS

Markers should ideally be stored horizontally and should be capped firmly

Nibs/Tips: Aubex 454 or similar (porosity over 65%)

Reservoir: De Martini CPE 2546 or similar (density 0,140-0,160 g/cm3)

Body: Polypropylene, Polyethylene **Cap:** Polypropylene, Polyethylene

It is recommended to thoroughly test the components selected.

HANDLING INSTRUCTIONS

Store between 15°C and 35°C. Do not expose loose ink to temperatures higher than 35°C. Protect from frost and avoid direct

sunlight. Storage temperatures above 35°C can result in reduced shelf life of the inks. After use clean the filling unit.

INSTRUCTION FOR USE

Stir ink in the drums well before use for at least 15-20 min. Keep the inks under stirring while filling markers in order to avoid pigment sedimentation.

Drums should be closed tightly during storage.

PACKING

50 KG net Plastic Drums 200 KG net Plastic Drums

Any and all statements, information and recommendations contained in the present technical sheet are drawn up to the best of the experience and knowledge of Reinol and based on tests which we regard as reliable. Nevertheless this does not imply any responsibility, either implicit or explicit, on the side of Reinol. Buyers shall bear all risks arising from the use of the products, it is therefore understood that the sale of the product is not protected by any guarantee, either implicit or explicit.